

STR - Science Technology Resources 5274 Scotts Valley Dr. #204 Scotts Valley, CA 95066

Toll free: (877) 395-1001 Fax: (866) 991-9591

www.strscopes.com sales@strscopes.com

ProScope HR2 Digital Microscope/Video Camera



The ProScope HR2 is a handheld video camera with interchangeable lenses that displays video images on any Macintosh or PC computer. The included software allows screen display and production of single frame captures, video movies and time lapse photography. Still image captures are high resolution at 2 mega pixels.

Applications: Education, Dentistry, Beauty, Hair Care and Cosmetology, Minerology, Gemology, and Jewelry, Textiles, Coin and Stamp Collecting, Forensics, Quality Control for almost any manufactured item, including circuit boards.

Simple...Powerful...Reliable...Cost Effective

Features

- Displays live video images, records snapshots, movies and time-lapse images. Time lapse fully programmable for duration and frequency.
- Portable (with laptop computer).
- "Touch & View" lenses allow you to magnify images by touching them with the microscope lens tip. Focuses instantly. No knobs to turn or squinting through an eyepiece.
- 14 Bayonet-mounted lenses available from 1x up to 400x. Regular, Hi-Resolution, polarized lenses available, and a microscope adaptor available. All except microscope adaptor have internal lighting.
- Optional accessories include stand, tripod, XYZ stage adapter, c-mount adapter, carrying case, collection and display set.
- Automatic white balance and exposure, manual control optional. Color adjustment controls allows fine tuning or artistic effects. LED brightness control.

System Requirements

PC: USB 2.0 Port (required for 2 mega pixel resolution), Windows XP (SP2), Pentium 4 or equivalent, a powered USB may be required on some systems

Mac: USB 2.0 Port (required for 2 mega pixel resolution), Mac OS 10.4.8+, 32 MB RAM, G4, G5 or Intel Mac, a powered USB may be required on some systems

Specifications

1/3-inch progressive 2 mega pixel color sensor Still Capture: 1600×1200 , 1280×1024 , 640×480 , or 320×240

Video Capture: 30fps at 320 x 240, 15fps at 640 x 480, 3.75fps at 1280 x 1024, 3.75fps at 1600 x 1200

Power source: USB 2.0 interface from computer (5V, 400 mA)

1.8m (6ft) cable, dimensions – 152mm x 45mm

Driver: USB Video Class – USB Human

Interface Device Class